

## Tool - CF 1000-1,5 120V - 1208209

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Automatic stripping and crimping device, 120 V version, for insulated taped ferrules with a cross section range of 0.5-2.5 mm<sup>2</sup> in acc. with DIN 46228-4: 1990-09

### Why buy this product

- Rugged design
- Quick change of cross section without the need for additional adjustments
- Up to 1200 conductors can be processed an hour
- Suitable for bulk processing
- The pull-out forces meet the requirements of IEC/EN 60999 and IEC/EN 60947
- The stripping and crimping machine can be used to process loose ferrules with insulating collars according to DIN 46228-4
- Quantity counter
- The conductor is stripped in a single step and crimped with a ferrule to a high standard of quality

### Key commercial data

|                        |   |
|------------------------|---|
| Packing unit           | 1   |
| Minimum order quantity | 1   |
| Catalog page           | Page 332 (CL2-2011)   |
| GTIN                   | <br>4 046356 011358 |
| Custom tariff number   | 84798100  |
| Country of origin      | GERMANY   |

### Technical data

#### General

|                                 |                      |
|---------------------------------|----------------------|
| Length (b)                      | 490 mm               |
| Height                          | 390 mm               |
| Width (a)                       | 240 mm               |
| Air consumption per compression | 1.2 l                |
| Working cycle                   | 1.5 s                |
| Weight                          | 29 kg                |
| Test standard                   | DIN 46228-4: 1990-09 |
| Compression                     | trapezoidal          |

# Tool - CF 1000-1,5 120V - 1208209

## Classifications

### eclass

|            |          |
|------------|----------|
| eCl@ss 4.0 | 21040301 |
| eCl@ss 4.1 | 21040301 |
| eCl@ss 5.0 | 21040301 |
| eCl@ss 5.1 | 21040301 |
| eCl@ss 6.0 | 17130101 |

### etim

|          |          |
|----------|----------|
| ETIM 2.0 | EC001186 |
| ETIM 3.0 | EC001186 |
| ETIM 4.0 | EC001186 |

### unspsc

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 27112118 |
| UNSPSC 7.0901 | 27111518 |
| UNSPSC 11     | 23171604 |
| UNSPSC 12.01  | 27111518 |
| UNSPSC 13.2   | 27111518 |

## Accessories

### Accessories

### Tools

Conversion kit - CF 1000-TOOLKIT 0,34/ 6 - 1208212



Assembly set for CF 1000, for insulated taped ferrules according to DIN 46228-4: 1990-09, cross section range: 0.25-0.34 mm<sup>2</sup>, AWG: 24-22, stripping length: 6 mm

Conversion kit - CF 1000-TOOLKIT 2,5/ 8 - 1208241



Assembly set for CF 1000, for insulated taped ferrules according to DIN 46228-4: 1990-09, cross section range: 0.5-2.5 mm<sup>2</sup>, AWG: 20-14, stripping length: 8 mm

Conversion kit - CF 1000-TOOLKIT 4,0/10 - 1208270



Assembly set for CF 1000, for insulated taped ferrules according to DIN 46228-4: 1990-09, cross section range: 4 mm<sup>2</sup>, AWG: 12, stripping length: 10 mm

## Tool - CF 1000-1,5 120V - 1208209

### Accessories

---

#### Conversion kit - CF 1000-TOOLKIT 0,34/ 8 - 1208225



Assembly set for CF 1000, for insulated taped ferrules according to DIN 46228-4: 1990-09, cross section range: 0.25-0.34 mm<sup>2</sup>, AWG: 24-22, stripping length: 8 mm

---

#### Spare knife - CF 1000 EM - 1205215

Accessories for CF 1000 stripping and crimping machine, replacement blade for 0.25 - 2.5 mm<sup>2</sup>, V-shaped

